



STAINLESS DESIGN DISPENSER

295

Touch-free
For foam soap
2-year warranty



Elegant and reliable foam soap dispenser. Stainless Design is a complete product line for commercial toilets, in which quality and aesthetics are paramount. The entire stainless product line is made of strong quality materials, featuring a unique design with a beautifully arched housing in brushed stainless steel.

Technical data

	Metric	Imperial
Type	STAINLESS DESIGN DISPENSER Prod. No.: 295 Touch-free dispenser for foam soap	STAINLESS DESIGN DISPENSER Prod. No.: 295 Touch-free dispenser for foam soap
Dimensions	H: 340 mm x W: 120 mm x D: 126 mm	H: 13.38" x W: 4.72" x D: 4.96"
Material	1.5 mm brushed stainless steel AISI 304	0.05" brushed stainless steel AISI 304
Capacity	800 ml = 1000–1300 dosages	0.21 gal = approx. 1000–1300 dosages
Viscosity	1 cP	1 cP
Battery operated	4 pcs. 1.5 V Alkaline batteries type AA	4 pcs. x 1.5 V Alkaline batteries type AA
Power supply	Optional power connection via external transformer	Optional power connection via external transformer
Net weight	2,4 kg	5.29 lb
Tender text	Touch-free soap dispenser for foam soap. Housing in 1.5 mm brushed, stainless steel, AISI 304. Capacity: 800 ml. Battery operated. Net weight: 2,4 kg. H: 340 mm x W: 120 mm x D: 126 mm /open housing: 350 mm	Touch-free soap dispenser for foam soap. Housing in 0.05" brushed, stainless steel, AISI 304. Capacity: 0.21 gal. Battery operated. Net weight: 5.29 lb. H: 13.38" x W: 4.72" x D: 4.96" /open housing 13.77"

Application

The STAINLESS DESIGN product line combines hygiene and durability with classic elegance to suit any commercial bathroom. The products are designed specifically for use in public toilets where low maintenance is called for, and equipment must be able to withstand rough treatment.

Referencer

Offices and administration, shopping malls, restaurants, hotels, airports, train stations, sports facilities and public swimming pools, schools, public institutions, and cultural centres.

Standard colour

Brushed stainless steel.
Also available in all RAL colours.

Power source option

6 Vdc transformer til 230V.

Installation

Wall mounting.

Activation

Intelligent sensor automatically adjusting the optimum activation distance. Dosage is activated when hand is held approx. 5 cm/1.96" underneath the dosing nozzle – dose is released only once per activation. LED light indicating when the dispenser is in use.

